



SPECIFICATION FOR COTCO LED LAMP

Document No: SPE/LC503PBG1-30Q-A3
Model No : LC503PBG1-30Q-A3
Rev. No: 03
Date: 2006-03-31


Description:

30 Degree 5mm LED Lamp in Bluish Green
Color with Water Transparent Lens and No
Stopper

Dice Material: InGaN

Confirmed
by Customer: _____

Date: _____



Applications:

- Advertising Signs
- Indicators
- Traffic

Absolute Maximum Ratings at Ta = 25°C


Items	Symbol	Absolute maximum Rating	Unit
Forward Current	I_F	25	mA
Peak Forward Current*	I_{FP}	100	mA
Reverse Voltage	V_R	5	V
Power Dissipation	P_D	100	mW
Operation Temperature	T_{opr}	-40 ~ +95	°C
Storage Temperature	T_{stg}	-40 ~ +100	°C
Lead Soldering Temperature	T_{sol}	Max.260°C for 3 sec Max. (3mm from the base of the epoxy bulb)	

*pulse width $\leq 0.1\text{msec}$ duty $\leq 1/10$

Typical Electrical & Optical Characteristics (Ta = 25°C)

Items	Symbol	Condition	Min.	Typ.	Max.	Unit
Forward Voltage	V_F	$I_F = 20\text{mA}$	---	3.4	4.0	V
Reverse Current	I_R	$V_R = 5\text{V}$	---	---	100	μA
Dominant Wavelength	λ_D	$I_F = 20\text{mA}$	500	505	510	nm
Luminous Intensity	I_V	$I_F = 20\text{mA}$	3000	4800	---	mcd
50% Power Angle	$2\theta_{\frac{1}{2}H-H}$	$I_F = 20\text{mA}$	---	30	---	deg

Dimension Drawing




Standard bins for LC503PBG1-30Q-A3 ($I_F = 20\text{mA}$):

Lamps are sorted to Luminous Intensity $-I_V$ & Dominant Wavelength $-\lambda_D$ bins shown.

Orders for LC503PBG1-30Q-A3 may be filled with any or all bins contained as below.

All Luminous Intensity $-I_V$ & Dominant Wavelength $-\lambda_D$ values shown and specified are at $I_F = 20\text{mA}$.



* W+ indicates Luminous Intensity is at W bin or above.

Important Notes:

- 1) All ranks will be included per delivery, rank ratio will be based on the Dices distribution.
- 2) Pb content <1000PPM.
- 3) Tolerance of measurement of luminous intensity is $\pm 15\%$.
- 4) Tolerance of measurement of dominant wavelength is $\pm 1\text{nm}$.
- 5) Tolerance of measurement of Vf is $\pm 0.05\text{V}$.
- 6) Packaging methods are available for selection, Please refer to PACKAGING STANDARD.
- 7) Please refer to LED LAMP RELIABILITY TEST STANDARD for reliability test conditions.
- 8) Please refer to APPLICATION NOTES for Application.

Graphs




FIG.1 FORWARD CURRENT VS. FORWARD VOLTAGE.




FIG.2 REVERSE CURRENT VS. REVERSE VOLTAGE.




FIG.3 RELATIVE LUMINOUS INTENSITY VS. FORWARD CURRENT




FIG.4 RELATIVE LUMINOUS INTENSITY VS. WAVELENGTH.




FIG.5 MAXIMUM FORWARD DC CURRENT VS AMBIENT TEMPERATURE ($T_{jmax}=105^{\circ}C$)




FIG.6 FAR FIELD PATTERN

Items	Signatures	Date
Prepared by	LiuZM	2006-03-31
Checked by	Aldosin	2006-03-31
Approved by	David	2006-03-31
FCN#	FCN20060081	

Revision History		
Rev. No	Date	Change Description
02	2005-07-05	Release.
03	2006-03-31	Cancel VF bin.

Data is subject to change without prior notice; please refer to COTCO Website for the latest version.

Copyright©2002 Cotco International Ltd.